




Remote Refrigerated Drop-In Wells

Models: CWBR-1, -2, -3, -4, -5, -6
CWBX-1, -2, -3, -4, -5, -6

Hatco's Remote Refrigerated Drop-In Wells keep pre-chilled food products at safe serving temperatures but in remote configurations that offer more flexibility in your particular dining design needs. Unique top angled inside wall design allows cold air to effectively blanket your food product to keep food optimally cold and fresh.

Standard features

- Top mount unit holds full-size pans in 1- to 6-pan configurations
- NSF 7 approved cold wall construction utilizes a refrigerant that keeps food product cold without drying it out



The unique angled inside wall design provides easy access and clear views. The greater surface area of the angled wall and the placement of the coils allow cold air to more effectively blanket your food product.

- Auto-defrost is activated through an advanced electronic controller programmed at the customer location
- 1" NPSM brass drain simplifies cleaning
- Matches the Hatco line of Wells for a full integrated look
- **CWBR models only:**
 - Condenser utilizes R-513A refrigerant
 - Include a condensing unit (shipped loose – can be field mounted up to 50' [15.24 meters] of tubing from unit) and control panel (shipped loose – probe wires are 9' [2.7 meters]) for installing in more convenient or desirable locations
- **CWBX models only:**
 - Includes a control panel (shipped loose – probe wires are 9' [2.7 meters]) but without a condensing unit for the increased flexibility of multiple cold well configurations

Project _____
Item # _____
Quantity _____



Remote models consist of these components shipped loose

Control panel (Shipped loose)

Condensing Unit CWBR-6 with a Condensing Unit (5/8 HP) and control panel (CWBX-6 with a control panel only)

Model CWBR-6 with accessory (hotel) food pans

Options (available at time of purchase only)

- ☐ Additional Four-Year Parts Only Warranty on the Compressor (CWBR only) at Time of Unit Purchase (Not available for export voltages)
- ☐ Slant Kit to give Cold Wells a 5° tilt
- ☐ EPDM Rubber Gasket (Factory installed and eliminates the need for silicone or other sealants)

Accessories

Pan Support Bars

- ☐ 12" (305 mm), hangs from 20" (508 mm) Pan Support Bar
- ☐ 20" (508 mm), hangs from pan shelf

Stainless Steel Food Pans:

- ☐ Third-Size (2.5" [64 mm] H)
- ☐ Half-Size (2.5" [64 mm] H)
- ☐ Full-Size (2.5" [64 mm] H)
- ☐ Full-Size (4" [102 mm] H)
- ☐ Full-Size (6" [152 mm] H)

- ☐ False Bottom (perforated false bottom)

Wire Trivets Stainless:

- ☐ Half-Size (10.19" [259 mm] W x 7.625 [194 mm] D)
- ☐ Full-Size (10.125" [259 mm] W x 18" [457 mm] D)



For operation, location and safety information, please refer to the Installation and Operating Manual.



HATCO CORPORATION

P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350



www.hatcocorp.com

customerservice@hatcocorp.com

[Find a Hatco Rep](#)

[Image Library](#)

[Document Library](#)



Remote Refrigerated Drop-In Wells

Models: CWBR-1, -2, -3, -4, -5, -6, CWBX-1, -2, -3, -4, -5, -6

Ordering Instructions:

Please specify the following with each order:

1. Desired Voltage and Hz:

120 (60 Hz),
220, 230 or 240V (50 or 60 Hz)

2. Number of Drop-In Wells Required:

1-, 2-, 3-, 4-, 5- or 6-pan as rectangular, full-size, 12" x 20", (305 mm x 508 mm)

3. Remote Refrigeration

NOTE: Shipped loose: Cold Well with Temperature Probe, Control Panel (Probe Wires are 9' (2.7 meters) and a TXV valve


A. CWBR with a Condensing Unit – may be field mounted up to 50' (15.24 meters) of tubing from the unit - shipped loose

B. CWBX without a Condensing Unit (Solenoid Valve attached to Cold Well)


Option

1. **Slant Option** for CWBR or CWBX-1, -2, -3, -4, -5 or -6
2. **EPDM Rubber Gasket** to eliminate need for silicone or other sealants

ALL MODELS, Slant Option (gray highlight)





ALL MODELS, False Bottom Accessory (1-part, 2- or 3-part, depending on pan size)



Models CWBR-, CWBX-Series


CWBR-6 (with Control Panel and Condenser Unit)

CWBX-6 (with Control Panel only)




Model CWBR only, Condensing Unit

May be field mounted up to 50' (15.24 meters) from unit



All Models Control Panel

May be field mounted up to 9' (2.7 meters) from unit



R-404 Condenser Dimensions for Remote Refrigerated Drop-In Wells (For Export Markets Only)

Model	Voltages	HZ	Width (A)	Depth (B)	Height (C)
CWBR-1, 2, 3, 4 CWBX-1, 2, 3, 4	120	60	14.62" (371 mm)	12.27" (312 mm)	11.37" (289 mm)
		50	13.64" (346 mm)	12.12" (308 mm)	11.37" (289 mm)
	220, 230, 240	60			
CWBR-5, -6 CWBX-5, -6	120	60	17.45" (444 mm)	16.35" (415 mm)	12.05" (306 mm)
	220, 230, 240	50/60	17.38" (441 mm)	13.10" (333 mm)	11.81" (300 mm)






Remote Refrigerated Drop-In Wells

Models: CWBR-1, -2, -3, -4, -5, -6, CWBX-1, -2, -3, -4, -5, -6

Cutout Dimensions for Remote Refrigerated Drop-In Wells



Model	Minimum Width (A)	Maximum Width (A)	Minimum Depth (B)	Maximum Depth (B)
CWBR-, CWBX-1	17.125" (435 mm)	18" (457 mm)	25.19" (640 mm)	26" (660 mm)
CWBR-, CWBX-2	30.125" (765 mm)	31" (787 mm)		
CWBR-, CWBX-3	43.125" (1095 mm)	44" (1118 mm)		
CWBR-, CWBX-4	56.125" (1425 mm)	57" (1448 mm)		
CWBR-, CWBX-5	69.125" (1756 mm)	70" (1778 mm)		
CWBR-, CWBX-6	82.125" (2086 mm)	83" (2108 mm)		

SPECIFICATIONS

Drop-In Full-Size Models - with Condensing Unit and Remote Control Panel

The shaded areas contain electrical information for International models

Model †	Dimensions (Width x Depth x Height) (12" [305 mm] Well Height)	Voltage	HP Compressor Size	Hz	Watts	Amps	Total Heat of Rejection (BTU/Hr)	Approx. Ship Weight
CWBR-1	19" x 27" x 12" (483 x 686 x 305 mm)	120	1/5	60	300	3.8	1288	131 lbs. (59 kg)
		220/230/240	1/3	50	1089/1190/1296	5.0/5.2/5.4	2475	
				60	1129/1234/1344	5.1/5.4/5.6	2557	
CWBR-2	32" x 27" x 12" (813 x 686 x 305 mm)	120	1/5	60	300	3.8	1528	160 lbs. (73 kg)
		220/230/240	1/3	50	1089/1190/1296	5.0/5.2/5.4	2715	
				60	1129/1234/1344	5.1/5.4/5.6	2797	
CWBR-3	45" x 27" x 12" (1143 x 686 x 305 mm)	120	1/5	60	300	3.8	1768	213 lbs. (97 kg)
		220/230/240	1/3	50	1089/1190/1296	5.0/5.2/5.4	2955	
				60	1129/1234/1344	5.1/5.4/5.6	3037	
CWBR-4	58" x 27" x 12" (1473 x 686 x 305 mm)	120	1/3	60	450	5.9	2519	200 lbs. (91 kg)
		220/230/240	3/8	50	826/904/984	3.8/3.9/4.1	2663	
			1/3	60	1129/1234/1344	5.1/5.4/5.6	3277	
CWBR-5	71" x 27" x 12" (1803 x 686 x 305 mm)	120	5/8	60	800	8.7	3954	271 lbs. (123 kg)
		220/230/240	1/2	50	826/904/984	3.8/3.9/4.1	2903	
			5/8	60	1956/2138/2328	8.9/9.3/9.7	5196	
CWBR-6	84" x 27" x 12" (2134 x 686 x 305 mm)	120	5/8	60	800	8.7	4194	313 lbs. (142 kg)
		220/230/240	1/2	50	826/904/984	3.8/3.9/4.1	3143	
			5/8	60	1956/2138/2328	8.9/9.3/9.7	5436	

† Models shipped with electronic temperature control and a condensing unit (all shipped loose) with a filter-drier and TXV valve.

◀ Single phase only

R-513A REFRIGERANT OPERATING SPECIFICATIONS IN 75°F (24°C) AMBIENT



Refer to the Installation section in the Installation and Operating Manual on the Hatco website

- Suction Pressure: 6-9 PSIG (0.4-0.6 Bar)
- Discharge Pressure : 115-125 PSIG (7.9-8.6 Bar)
- Superheat: 4-10°F (2.2° to 5.6°C)
- Subcooling: 5-10°F (2.8° to 5.6°C)

RECOMMENDED FACTORY FILL RATES for R-513A REFRIGERANT

(CWBR Condensers are shipped without refrigerants)

Model	Fill Weight
CWBR-1	1 lb. 15 oz. (0.879 kg)
CWBR-2	2 lb. 1 oz. (0.936 kg)
CWBR-3	
CWBR-4	1 lb. 15 oz. (0.879 kg)
CWBR-5	2 lb.13 oz. (1.276 kg)
CWBR-6	

HATCO CORPORATION

P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(414) 671-6350



www.hatcocorp.com

customerservice@hatcocorp.com

[Find a Hatco Rep](#)

[Image Library](#)

[Document Library](#)



Remote Refrigerated Drop-In Wells

Models: CWBR-1, -2, -3, -4, -5, -6, CWBX-1, -2, -3, -4, -5, -6

SPECIFICATIONS

Drop-In Wells Full-Size Models - with Remote Control Panel (without a Condensing Unit)

The shaded areas contain electrical information for International models

Model †	Dimensions (Width x Depth x Overall Height)	Volts	HZ	Evaporator Load (BTU/Hr)	Approx. Ship Weight
CWBX-1	19" x 27" x 17.05" (483 x 686 x 433 mm)	120	60	330	94 lbs. (43 kg)
		220/230/240	50/60		
CWBX-2	32" x 27" x 17.05" (813 x 686 x 433 mm)	120	60	630	123 lbs. (56 kg)
		220/230/240	50/60		
CWBX-3	45" x 27" x 17.05" (1143 x 686 x 433 mm)	120	60	930	150 lbs. (68 kg)
		220/230/240	50/60		
CWBX-4	58" x 27" x 17.05" (1473 x 686 x 433 mm)	120	60	1230	176 lbs. (80 kg)
		220/230/240	50/60		
CWBX-5	71" x 27" x 17.05" (1803 x 686 x 433 mm)	120	60	1530	211 lbs. (96 kg)
		220/230/240	50/60		
CWBX-6	84" x 27" x 17.05" (2134 x 686 x 433 mm)	120	60	1830	250 lbs. (113 kg)
		220/230/240	50/60		

† Models shipped with electronic temperature control, TXV (all shipped loose) and a solenoid valve attached to well.

PRODUCT SPECS

Remote Refrigerated Drop-In Wells

The NSF 7 approved Remote Refrigerated Drop-in Well shall be a Model ... as manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The Refrigerated Drop-in Well shall be rated at ... watts, ... volts, ... hp, and be inches (millimeters) in overall width and be ... inches (millimeters) in overall depth. It shall utilize R-513A refrigerant and consist of aluminized steel housing with a stainless

bezel, an electronic temperature control, pan support bars for full-size pans and with or without a condensing unit (compressor, sight glass, service valves, receiver, and filter-drier). Accessories may include pan support bars, false bottoms, trivets and stainless steel food pans.

Warranty consists of 24/7 parts and service assistance (U.S. and Canada only).

HATCO CORPORATION

P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(414) 671-6350



www.hatcocorp.com

customerservice@hatcocorp.com

[Find a Hatco Rep](#)

[Image Library](#)

[Document Library](#)